



UV Resistant Industrial Cable Tie, 200X3.6mm, Black, Indoor/Outdoor, 100PK

Basic data:	
ID	0000460063
GTIN	7630268403188
GTIN	7630268403188



Features:

These nylon cable ties are designed to withstand rough installation practices that occur in MRO and construction projects. They also help to provide superior bundle tightness, excellent tensile strength, and flexibility. Recommended for bundling wire, cable, or hose, enhanced UV resistant performance help a consistent application under long sun expose enviroment

Technical data:	
Band width:	3.6 mm
Length belt/tape/tie:	200 mm
Tie thickness:	1.15 mm
Max. bundle diameter:	52.5 mm
Min. bundle diameter:	3.5 mm
Min. tensile strength:	180 N
Operating temperature:	-40 85 °C
Mounting temperature:	-20 85 °C
Model:	Internal toothing
Band closure:	Plastic lip/-cam
Material:	Plastic
Material quality:	Polyamide (PA)
Surface protection:	Untreated
UV-stable according to ASTM D6779:	Yes
Halogen free:	Yes
Colour:	Black
Text strip:	None
Type of fastening:	None
UL approval:	Yes
luff - u-u bilife l fi in l - fi	V2

Inflammability class of insulation material according to UL94